



GEHAEUSE: PP, SCHWARZ  
HOUSING: PP, BLACK

|   |     |  |                   |
|---|-----|--|-------------------|
| KUNDENMERKE / CUSTOMER NOTICES  |     | ISO 128  |                   |
| FORM- UND LAGETOLERANZEN<br>TELEMETRIENORM UND<br>WARTUNGSANLEITUNG<br>NACH ACCORD. TO ISO 1411 |     | Eisässer Industrietechnik GmbH   |                   |
| OBERFLÄCHENRUFACES<br>NACH ACCORD. TO ISO 1502  |     | ANGEBOTSZEICHNUNG<br>CUSTOMER DRAWING  |                   |
| WENIGSTENABMESSUNGEN<br>NACH ACCORD. TO ISO 13715   |     | SCHUTZMERK ISO 18016 BEACHTEN / REFER TO PROTECTION NOTICE ISO 18016   |                   |
| MASSE OHNE TOLERANZANGABEN:<br>DIM. WITHOUT TOLERANCES:   |     | THE REPRODUCTION, DISTRIBUTION AND UTILIZATION OF THIS DOCUMENT AS<br>WELL AS THE COMMUNICATION OF ITS CONTENTS TO OTHERS WITHOUT EXPLICIT<br>AUTHORIZATION IS PROHIBITED. OFFENDERS WILL BE HELD LIABLE FOR<br>THE PAYMENT OF DAMAGES. ALL RIGHTS RESERVED IN THE EVENT OF THE<br>GRANT OF A PATENT, UTILITY MODEL OR DESIGN. |                   |
| LAENGEN<br>LENGTHS  | ±2  | DATUM<br>DATE  | BENENNUNG / NAME  |
| RADIEN<br>RADIUS  | --  | BEARB./DRAWN   | 21.09.2005 GRUBER |
| FASEN<br>CHAMFERS   | --  | GEPR./CHECK.   | 22.09.2005 KOPEC  |
| WINKEL<br>ANGLE   | ±0° | GESEH./APP.  | 22.09.2005 KOPEC  |
| PROGRAMM-NR. / PROGRAM NO.  |     | MANN+HUMMEL GMBH<br>D-71631 LUUDWIGSBURG   |                   |
| POS.  |     | ZEICHNUNGS-NR.<br>DRAWING NO.  |                   |

|   |  |                        |                                    |
|---|--|------------------------|------------------------------------|
| 4 | RING<br>RING                                     | 45 100 23 109          | ERSATZTEILLISTE / SPARE PARTS LIST |
| 3 | STAUBENTLEERVENTIL<br>DUST DISCHARGE VALVE       | 39 000 40 102          |                                    |
| 2 | FILTERELEMENT<br>FILTER ELEMENT                  | C 11 100               |                                    |
| 1 | GEHAUSE UNTERTEIL VST<br>HOUSING BOTTOM ASSEMBLY | 45 100 17 969          |                                    |
|   | BENENNUNG<br>NAME                                | BEHELL-NR.<br>PART-NO. | FREID-NR.<br>CUSTOMER-NO.          |

STUTZENLAGE 'A' ZU VENTILAGE 'B' RADIAL IN 3° SCHITTEN RASTBAR  
GERAET FUER STEHENDEN UND LIEGENDEN EINBAU  
AUSTRAGSOEFFNUNG AM VENTIL UNTEN  
FILTER INTAKE 'A' TO POSITION OF VALVE 'B' POSSIBLE LOCKING EVERY 3° (RADIAL)  
UNIT FOR STANDING AND LYING INSTALLATION  
DUST VALVE IN BOTTOM POSITION