



STUTZENLAGE 'A' ZU VENTILLAGE 'B' IN 1=3' SCHRITTEN RASTBAR
GERAET FUER LIEGENDEN EINBAU
AUSSTRAGSOEFFNUNG AM VENITIL UNTEN

FILTER INTAKE 'A' TO POSITION OF VALVE 'B' LOCK IN 1=3'S STEPS
UNIT FOR LYING INSTALLATION
DUST VALVE IN BOTTOM POSITION

5	RING RING	45 400 23 109	
4	STAUBENTLEERVENTIL DUST DISCHARGE VALVE	39 000 40 391	
3	SEKUNDÄRELEMENT SECONDARY ELEMENT	CF 400	
2	HAUPTELEMENT MAIN ELEMENT	C 16 400	
1	GEHAUSE U-TEIL VST HOUSING BOTTOM CPL.	45 400 17 699	
POS.	BENENNUNG NAME	BESTELL-NR. PART-NO.	FREMD-NR. CUSTOMER-NO.

ERSATZTEILLISTE / SPARE PARTS LIST

GEHAUSE: PP, SCHWARZ
HOUSING: PP, BLACK

CAD-ZEICHNUNG
CAD-DRAWING
BEARBEITUNG NUR AUF CAD-SYSTEM
CHANGE ONLY ON CAD-SYSTEM

OBERFLAECHE / SURFACES NACH / TO ISO 1302		KUNDENVERMERKE / CUSTOMER NOTICES	
FORM- UND LAGETOLERANZEN TOLERANCES OF FORM AND POSITION NACH / TO ISO 1101		ISO 128	ANGEBOTSZEICHNUNG CUSTOMER DRAWING
WERKSTUECKKANTEN WORKPIECE EDGES NACH / TO DIN 6784		MASS-STAB SCALE 1:2	
MASSE OHNE TOLERANZANGABEN: DIM. WITHOUT TOLERANCES:		IF-E1	SCHUTZVERMERK DIN 34 BEACHTEN / PROTECTION NOTICE TO DIN 34 COPYING OF THIS DOCUMENT, AND GIVING IT TO OTHERS AND THE USE OR COMMUNICATION OF THE CONTENTS THEREOF, ARE FORBIDDEN WITHOUT EXPRESS AUTHORITY. OFFENDERS ARE LIABLE TO THE PAYMENT OF DAMAGES. ALL RIGHTS ARE RESERVED IN THE EVENT OF THE GRANT OF A PATENT OR THE REGISTRATION OF A UTILITY MODEL OR DESIGN.
LAENGEN LENGTHS	± 2	DATUM DATE	
RADIEN RADI	± /	BEARB. / DRAW	BOESEN
FASEN CHAMFERS	± 2°	GEPR. / CHECK	OELPKE
WINKEL ANGLE	± 2°	GESEH. / APP.	OELPKE
CAD-ZEICHNUNG CAD-DRAWING		 ZEICHNUNGS-NR. DRAWING-NO. 45 402 92 911 00	
ERSATZTEILLISTE / SPARE PARTS LIST		ERSATZ FUER / SUBSTITUTE OF 45 402 92 910	